


1	Type	Low Distortion Lens	
2	Resolution	10MP	
3	Image Format	1/2.3"	
4	Image Circle	φ8.0mm(V-MAX)	
5	EFL	7.2mm	
6	TTL	37.87mm	
7	F/NO.	2.4	
8	FFL (M)	6.23mm	
9	BFL (O)	7.23mm	
10	For Sensor	1/2.3"	
11	F.O.V	Horizontal	47°
12		Vertical	37°
13		Diagonal	57°
14	TV Distortion	<-1.5%	
15	Relative Ill.	---	
16	Chief Ray Angle	<12°	
17	M.O.D	0.3m~∞	
18	Mount Type	M12*P0.5	
19	Dimension Figure	φ19.00*L26.14mm	
20	Lens Structure	10G	
21	IR-Filter	T=50%&IR650±10nm	
22	Waterproof	No	
23	Weight	---	
24	Iris Operation	Fixed	
25	Zoom Operation	Fixed	
26	Focus Operation	Manual	
27	Operating Temperature	-20° ~+85°	
28	Storage Temperature	-20° ~+85°	



Scale	Remark	Tolerances	Date	Revised		福州创安光电科技有限公司 FUZHOU CHUANGAN OPTICS CO., LTD
4:1	X	±0.2	2021-07-09	CH1106A Rev1.0		
	X.0	±0.15				
Units	X.00	±0.10	Design	Linda	2020-03-26	
	X.000	±0.001	Checked	Anna	2020-04-20	
mm	Angle	±0.5°	Approval	Sanmu	2020-05-13	

